

Control Keyboard Model: AU25MZ



Product Introduction:

The AU25MZ uses an embedded 2.5" LCD so you can check the real-time operational motion of the camera. Using this controlling keyboard you can expediently control and set up the speed dome camera, Controlling all functions of the camera such as Pan, Tilt Zoom, Light, Wiper, etc...

Products feature:

- 2.5" color LCD screen, 1 channel video input and 1 channel video output
- 3-Axis joystick, it can achieve various speed control and zoom functions
- 16 protocols, Multi-protocol baud rate range: 2400Bps - 19200Bps
- RS-485 communication, Control distance range to 1200m, Compact
- It can control multi front end equipment, including intelligent Dome Camera, decoder, processor, etc...

Technical parameters, Specifications: AU25MZ

Communication Baud rate:	1200bps, 2400bps, 4800bps, 9600bps, 19200bps, RS485 control
Communication distance:	≤1200M
Video format:	PAL/NTSC
Video input:	1Vpp/75Ω,Compound(BNC)
Video output:	1Vpp/75Ω,Compound(BNC)
Work temperature:	-25°C - 50°C
Power supply:	DC9 - 16V
Consumption:	≤8W
Size:	210 (W) x 1300 (D) x 55 (H) mm (85 (H) from base to top of joystick)