

WECU-CV-SD

Key Features:

- 1/3" CCD Sensor
- High Resolution - 550 TV Lines (Color), 600 TV Lines (B/W)
- Day/Night Function with ICR
- 36 IR LED Module
- Separate Camera Control Board
 - OSD Menu
 - Service Monitor Output
- 12VDC/24VAC Dual Voltage
- Lens: 3.8~9.5mm, DC Auto Iris
- Exterior / Interior Application

Construction:

- 4" Polycarbonate Bubble
- 3-Axis Gimbal
- Flush Mount Housing w/ Surface Mount Plate in a single package
- Impact Resistant Dome w/ Aluminum Housing
- Aluminum Wall Mount (Option)
- Weatherproof - IP66
- Fan & Heater(Option)
- Compact Size

Specifications:

- Video Formats: NTSC | PAL
- Image Sensor: 1/3" SONY CCD
- Sync System: Internal / Line Lock(Optional)
- Scanning system: 525 Lines, Interlaced 625 Lines, Interlaced
- Electronic Shutter: 1/60 ~ 1/100,000 1/50 ~ 1/100,000
- Main Video Output: 1.0 Vp-p Composite, 75 ohm
- Service Monitor Output: 1.0 Vp-p Composite, 75 ohm
- Horizontal Resolution: 550 TV Lines(Color), 600 TV Lines(B/W)
- Min. Illumination: 0.1 Lux(Color), 0.01 Lux(B/W), 0.002 Lux(DSS On)
- S/N Ratio: More than 50dB(AGC Off)
- Day/Night Function: ICR
- 36 IR LEDs: LED Distance: up to 100 ft.
- Lens (DC Auto Iris): Vari-focal: 3.8~9.5mm
- Auto Iris Control: DC Level Button
- Camera Control & Setup: OSD Menu
- Operating Temperature: -5°C ~ +45°C(Normal), -25°C ~ +60°C(w/ Fan & Heater)
- Operating Humidity: Within 90% RH
- Weatherproof: IP66(Only applies to Vandal proof Housing)
- Power Consumption: Camera - 500mA, Fan & Heater - 20VA(24VAC Only), 1Amp(w/ LED On)
- Power Requirement: 12VDC/24VAC Dual Voltage



Easy Camera Setup

Camera Control Board is conveniently located at the base of Dome Housing. Service Monitor Output, DC Level Button and Dip Switches are easily accessible for quick camera setup.



Easy Gimbal Adjustment

Traditional Dome Insert has been fully integrated into the Gimbal for complete camera concealment. Uniquely designed Gimbal mechanism yields maximum lens rotation & placement (85° Tilt, 355° Pan), in quick and simple steps.



Easy Housing Installation

Either flush mount or surface mount application, pre-drilled mounting holes on EasyView Domes accommodate various electrical junction boxes, making installation easy and less time consuming.



Flush Mount



Surface Mount Plate

WECU Surveillance.com

P.O. Box 158

Carstairs, Alberta, Canada T0M0N0

Ph: 403.668.4758

Fax: 403.668.4790

Email: info@wecusurveillance.com

Website: <http://www.wecusurveillance.com>